


Building Airflow Setups Resilient to Zonal/Regional Down Events

Khaled Hassan



Agenda

- The Resilience Problem
- Triggers of the problem
- Mitigation Strategies
- Conclusion
- QA



The Problem




The Problem: Vulnerability to Physical Failures

- Using Airflow as a solution for your business
- Physical failure (e.g. power/network outage)
- Running software behaviour during the outage in two aspects:
 - Physically How and where are the critical infrastructure components located.
 - Software How DAGs are prone to these failures




Mitigation Strategies

- Retries should be enabled
- Infrastructure
 - Deployments Replication
 - Deployments Spread
 - Data Replication
- DAG Implementation
 - DĀGs statelessness
 - DAGs idempotency
 - DAGs dependencies replication
- Complementary Strategies One on its own may not be sufficient.



Mitigation Strategy 1: Replication Of Critical Components



Deployments Replication

- Critical Deployments (e.g. Workers, Schedulers, Internal API in AF3)
- Failovers to healthy replicas during failures

• **Data Replication -** Airflow DB


- Ensure that healthy replicas can always access needed data
- Replicating DBs might be more challenging than workloads


Real Life Scenario 1



- Identical server rooms (2 Failure Domains):
 - o Failure Domain 1: Room A contains
 - Scheduler Replica 1
 - DB Replica 1
 - **Worker Replica 2**
 - AF3: Internal API Replica 2
 - Failure Domain 2: Room B contains
 - Scheduler Replica 2
 - DB Replica 2
 - Worker Replica 1
 - AF3: Internal API Replica 1
- Only Room A Loses Power
- Potential Problem: Building-wide Power Outage?

Mitigation Strategy 1: Replication Of Critical Components





Potential Problem - What if both Rooms share the same infrastructure (e.g. power/network)?

Mitigation Strategy 2: Spread of replicated components

- Mitigation of Zonal/Regional Outages
- Enhanced Availability
- Zonal/Regional Disaster Recovery

- Cloud solution example:
 - Components are workloads in Kubernetes

 Defining topologySpreadConstraints in kubernetes

```
topologySpreadConstraints:
```


- maxSkew: 1

topologyKey: topology.kubernetes.io/zone


Real Life Scenario 2

- Room A is now in Building A and Room B is in Building B
- Each building now is a failure domain
- Whole Building A loses Power

 Continuity of processes hence continuity of business



Stateless DAG




Mitigation Strategy 2: DAG Implementation

- Stateless DAGs
- Idempotent Operations
- Replicated Dependencies

DAG Strategy 1: Stateless DAGs


- Stateful Definition
- Stateless Definition

- Why is Statefulness a Problem?
 - Lost Progress
 - Inconsistent State on retries
 - Failover Issues




DAG Strategy 2: Idempotent Operations

- What is Idempotency?
- Why Idempotency is Crucial for Reliability?
 - Preventing Duplication
 - Simplified Recovery after failures



DAG Strategy 3: Replicating DAG Dependencies

- External State & Single Points of Failure
 - DAGs often depend on external systems (storage, databases, services).
 - Replication of dependencies is crucial.



Cloud Composer

- Managed Airflow Environment
- High Resilience Configuration
 - Minimum Number of Replicas

Underlying Infrastructure Handled automatically.





Conclusions

- If availability is crucial for your business:
 - Replication and Spread is crucial for critical components
 - DAGs implementation analysis is crucial (Idempotency, Statelessness, etc)
- Resilience comes with a trade off:
 - Cost
 - Complexity
 - Sometimes latency
- Larger scale failures are sometimes inevitable

Questions?

hkhaled@google.com