
## Seamless Airflow Upgrades: Migrating from 2.x to 3




## Why Upgrade to Airflow 3?



Run anywhere, in any language



Scheduler-man aged backfills



Modern UI & UX




Event driven scheduling &

**Data assets** 



Task SDK



Lean core and Providers



**DAG Versioning** 



Security upgrades



Seamless upgrades



**Edge Executor** 



Inference and hyperparameter tuning



Developer experience

## Seamless Airflow 3 Upgrade: Step-by-Step Checklist

- Take care of the Prerequisites
- Dackup & Clean your existing Airflow instance
- Verify DAG Compatibility using Ruff
- Update Airflow Configuration
- OS Address known Breaking Changes
- Upgrade and test in Development
- Production Upgrade
- Post-Upgrade Validation



## Step 1: Versions Check and Prepare for upgrade



#### **Airflow Version:**

Must be 2.6.3 or higher (ideally 2.7.x) for a smooth Airflow 3 upgrade path



#### **Python Version:**

Airflow 3 requires

Python 3.9+; support

for 3.7 and 3.8 is

dropped



#### **Database Compatibility:**

Metadata DB must be
PostgreSQL 13+ or MySQL
8+ due to SQLAlchemy 2.x
migration



#### **Providers &**

Dependencies: Install
apache-airflow-provider
s-standard plus any
additional DAG providers
needed



Astronomer users
benefit from managed
runtimes; open-source
users must verify and
upgrade manually

## Step 2: Clean and Back Up Your Existing Airflow

#### Instance



#### **Backup Your Database**

Make a backup of your Airflow metadata database before starting the migration. Shut down Airflow instances if no hot backup is available to ensure consistency.



#### **Avoid Migration Risks**

A backup prevents issues from failed migrations or network interruptions that could leave your system in a half-migrated state.



#### **Clean Up Old Data**

Use the airflow db clean CLI command to remove unnecessary data like old XComs to reduce database size and speed up schema changes.



#### **Resolve DAG Errors**

errors remain, such as
AirflowDagDuplicatedIdExcepti
on. Run airflow dags reserialize
without errors before
proceeding.



# Step 3 – Ensure DAG Code Compatibility with Ruff



Install Ruff v0.13.1 or later: pip install --upgrade ruff



Run lint checks for breaking changes: `ruff check dags/ --select AIR301`.



Preview automated corrections with `--show-fixes` to verify suggested code updates



Apply safe fixes instantly using `--fix`, updating imports and parameters without manual edits



Use `--fix --unsafe-fixes` cautiously for import path changes that may alter behavior



Re-run checks until no AIR rule violations remain, confirming code is fully upgraded



Astronomer users can execute 'astro dev upgrade-test' to automate all steps including dependency verification

#### Ruff Rules for Airflow 3 Upgrade

## AIR30 Rules (Mandatory)

- 1. Check for removed parameters and imports no longer available in Airflow 3
- 2. Mandatory changes to ensure DAGs function correctly in Airflow 3

#### **AIR31 Rules**

- 1. Check for deprecated parameters and imports still available in Airflow 3
- 2. Recommended changes to maintain compatibility with future Airflow versions

#### Airflow OSS Ruff linter vs. Astro CLI

#### **Using Ruff Linter (OSS)**

- 1. Install the latest Ruff linter via pip: `pip install --upgrade ruff`
- 2. Run Ruff on your DAG code: `ruff check --preview --select AIR30 `
- 3. Use `--fix` flag to automatically fix some mandatory issues
- 4. Ruff outputs errors with suggestions, e.g., renaming deprecated DAG params like 'fail\_stop' to 'fail\_fast'. Fix the mandatory issues.
- 5. Requires manual review of breaking changes and Airflow release notes for full compatibility

#### **Using Astro CLI**

- 1. Run `astro dev upgrade-test` which also includes Ruff linter as part of command and fix the ruff issues.
- 2. Automatic detection of Airflow 3 compatibility issues within Astro environment

#### Step 4: Check and fix breaking Airflow configs



Upgrade to **Airflow 2.11.0** as **airflow config update** is available from this version.



Run airflow config update to detect deprecated, moved, or invalid configs in airflow.cfg



Review both **breaking** and **recommended** config changes



Use airflow config update --fix to auto-apply fixes with backup creation for old airflow configuration file

```
The following are the changes in airflow config:

- [BREAKING] Updated default value of 'core/executor' from 'SequentialExecutor' to 'LocalExecutor'.

- [BREAKING] Removed 'logging/log_filename_template' from configuration.

- [BREAKING] Renamed 'webserver/web_server_host' to 'api/host'.

- [BREAKING] Renamed 'webserver/web_server_port' to 'api/port'.

- [BREAKING] Renamed 'webserver/workers' to 'api/workers'.

- [BREAKING] Renamed 'webserver/web_server_ssl_cert' to 'api/ssl_cert'.

- [BREAKING] Renamed 'webserver/web_server_ssl_key' to 'api/ssl_key'.

- [BREAKING] Renamed 'webserver/access_logfile' to 'api/access_logfile'.


- [BREAKING] Renamed 'default value of 'scheduler/catchup_by_default' from 'True' to 'False'.

- [BREAKING] Renamed 'scheduler/dag_dir_list_interval' to 'dag_processor/refresh_interval'.

- [BREAKING] Renamed 'triggerer/default_capacity' to 'triggerer/capacity'.

Dry-run is mode enabled. To apply above airflow.cfg run the command with `--fix`.
```

### Types of Airflow 3 configuration changes



## Step 5 – Assess Breaking Changes

**Direct DB Access Removed:** Replace task code that opens DB sessions or queries metadata directly with Airflow public APIs or REST calls.

**Scheduling & Timetables Changes:** Replace `schedule\_interval` with `schedule`. New cron triggers disable automatic backfills by default; enable with `scheduler create\_cron\_data\_intervals=True`.

**Execution Date Context:** Update DAGs to replace `execution\_date` and related variables with `logical\_date` and `data\_interval\_start/end`.

**Removed Features:** Migrate from SubDAGs to TaskGroups or Datasets; replace SLA miss alerts with external monitoring; update plugins to new system as FAB-based plugins need compatibility provider.

**XCom Serialization:** Disallow pickled XComs by default for security. Migrate to custom backends. Old pickled XComs archived during DB migration.

**Provider Changes:** Operators and hooks moved to separate provider packages requiring explicit installation.

### Step 6 - Upgrade & Test Airflow 3 Locally

01 02 03 04 05

Set up a local or staging Airflow environment

Upgrade Airflow
to version 3,
apply all config
and DAG code
changes, then run
airflow db
upgrade to
migrate metadata
schema

Start Airflow 3
components: API
server replaces
webserver; run
dag-processor
alongside
scheduler

Trigger and
monitor all critical
DAGs, verifying
task execution,
scheduling,
XComs, and
templated
variables

Fix errors
iteratively and
re-test until all
DAGs run cleanly

### Upgrade and Test locally (OSS method)

#### **Install Airflow 3**

Install Airflow 3 (e.g., pip install apache-airflow==3.0.0 with constraints, or use the official Airflow 3 Docker image). Apply the same configuration changes using the updated airflow.cfg and include the DAG code fixed via Ruff.

## Run Ruff linter and airflow config update

Run Ruff's AIR rules linter to identify breaking code changes. Use airflow config update tool to migrate config files to Airflow 3 format.

#### Database Migrations

Run database migrations with airflow db upgrade (equivalent to airflow db migrate) to upgrade the metadata DB schema.

#### **Change your startup script**

Run airflow api-server and airflow dag-processor

#### Run airflow and test the DAGs

Run database migrations with airflow db upgrade (equivalent to airflow db migrate) to upgrade the metadata DB schema.

## Demo Upgrade and Test locally (OSS method)

### Upgrade and test locally: Using astro cli

01 02 03 04

#### **Update Astro Project**

Change your Astro project's

Dockerfile base image to the
new Astro Runtime (Airflow 3)
tag from astronomer.io.

## Run upgrade compatibility tests and fix

Use Astro CLI command 'astro dev upgrade-test
--runtime-version ' to run compatibility tests including dependencies.

#### **Start Airflow 3 locally**

Execute 'astro dev start' or 'astro dev restart' to launch Airflow 3 locally with your project's DAGs and config.

### Verify Local Setup and Run DAGs

Access the Airflow 3 web UI at http://localhost:8080 to verify that components like API server, scheduler, triggerer, and local Postgres are running.

## Demo Upgrade and test locally: Using astro cli

## Choose Your Production Upgrade Strategy: Blue-Green vs In-Place

## Blue-Green Deployment (Recommended)

- Set up new Airflow 3
   environment alongside
   existing Airflow 2
- Deploy updated DAGs and config with fresh or migrated metadata DB
- 3. Test fully before switching traffic to Airflow 3 to minimize downtime
- 4. Supports easy rollback by switching back to Airflow 2
- 5. Astronomer users can upgrade via UI or CLI seamlessly
- 6. Open-source users must provision new infrastructure and handle DB migration

## In-Place Upgrade (Advanced)

- Upgrade existing environment by installing Airflow 3 and migrating live DB
- 2. Requires downtime during migration and service restarts
- 3. Rollback is complex
- Must update service scripts for new API server and dag-processor

#### Essential Q&A & Upgrade Resources



**Astronomer's Upgrade Guide (Airflow 2 → 3)** 



**Astronomer Support & Community Slack** 



Official Apache Airflow Documentation – "Upgrading to Airflow 3"



**Apache Airflow Slack Channel (#airflow-upgrade)** 



Astral (Ruff) Airflow Rules Documentation: Details on AIR301, AIR302 (mandatory) and AIR311, AIR312 (recommended) linter rules

## QUESTION?

# The 2025 Apache Airflow® Survey is here!

Fill it out to get a free Airflow 3
Fundamentals or DAG Authoring in
Airflow 3 certification code

